

Anritsu envision : ensure

OTA Product Catalog

Shield Box	MA8161A
RF Chamber	MA8171A
CATR Anechoic Chamber	MA8172A





OTA Products



for 5G NR DUT Tests

5 G network testing is not the same as testing 4G architectures, or any other previous wireless network type.

Traditionally, network engineers confirm base transceiver stations (BTS) and antennas are functioning properly and transmitting the design signal strength by connecting test instruments using a coaxial cable to the base station RF connector.

However, new 5G services use the sub-6 GHz and mmWave bands, and 3GPP recommends using over-the-air (OTA) call connections to test the mmWave band, requiring an OTA RF chamber for stable measurement.

Anritsu's reasonably priced OTA products support this wide frequency band with easy setup for shorter test times.

*DUT=Device under test



Anritsu OTA Products Features

Wide Product Line Supporting Function to 3GPP Conformance Tests

MA8161A Shield Box

Supports simple OTA test environment for 5G/LTE protocol R&D tests, PCT/CAT pre-tests, etc.

- Small footprint for easy benchtop use and good handling
- Regression testing, etc., for 5G UE development stage
- Supports both sub-6 GHz and mmWave bands



MA8171A RF Chamber

Supports OTA environment for integrated RF/protocol tests, such as 5G NR mmWave beamforming management tests, etc.

- For development of 5G NR chipsets and devices as well as UE mmWave development
- Supports 5G NR mmWave RF ERP/TIRP measurements, etc.
- Both 5G NR Standalone (SA) and Non-standalone (NSA) modes



MA8172A CATR Anechoic Chamber

Supports 5G NR OTA environment using 3GPP-compliant Compact Antenna Test Range (CATR) method


- For mmWave development of 5G NR chipsets and devices, and UE conformance tests
- Supports 5G NR mmWave spurious tests
- Three component parts for easy transport and quick setup



Anritsu OTA Products Layout

Shield Box MA8161A

Front



Rear




- 1** SMA (f) connector × 8
- 2** Through hole × 2
- 3** Ventilation hole × 2
- 4** K (f) connector × 8

* Example selecting MA8161A-002

Anritsu OTA Products Layout

RF Chamber MA8171A

Setup Example



1 RF Chamber MA8171A

2 28 GHz RF Converter MA80001A/
39 GHz RF Converter MA80002A

3 Converter Rack B0747A

4 Chamber Rack B0746A

5 Radio Communication Test Station MT8000A

6 Position Controller MA8174A

Door Opening



7 Test Antenna

8 Positioner MA8175A

Anritsu OTA Products Layout


CATR Anechoic Chamber MA8172A

Front



- 1 Door
- 2 Sealing handles
- 3 Handle
- 4 Ventilation hole
- 5 Position Controller MA8178A

Enlarged View





- 6 Connect to MA8178A (Theta/Phi)
- 7 USB3.0
- 8 Connect to MT8000A (5, 6)
- 9 For LTE Link Antenna
- 10 Through Hole 1
- 11 Through Hole 2
- 12 LAN
- 13 RF I/O
- 14 Through Hole 3
- 15 Connect to MT8000A (1, 2, 3, 4)

Anritsu OTA Products Layout

CATR Anechoic Chamber MA8172A (continued)

Insides



- 1 Feed antenna
- 2 Positioner MA8179A
- 3 LTE Link Antenna Kit MA8172A-AK023
- 4 Reflector
- 5 NR FR2 Link Antenna Kit MA8172A-AK022

Rear



- 1 Ventilation hole
- 2 Fans

Anritsu OTA Products Specifications

Shield Box MA8161A

Shield Box MA8161A

Electrical Characteristics	Shielding characteristics: without cable connection via USB connector or Through Hole ≥50 dB (600 MHz ≤ frequency ≤ 6 GHz) ≥50 dB (24 GHz < frequency ≤ 43.5 GHz) (nom.)	
Input/Output Connector	When Connector Panel 1 MA8161A-001 is selected SMA (f) — SMA (f): 2 K (f) — K (f): 2 USB 3.0 Type-A (f) — USB 3.0 Type-A (f): 1 When Connector Panel 2 MA8161A-002 is selected SMA (f) — SMA (f): 8 K (f) — K (f): 8 Through Hole: 2	
Dimensions and Mass	Outer dimensions: 434 (W) × 271 (H) × 328 (D) mm (excluding projections) Mass: ≤16 kg (Full option configuration) Maximum test UE size: 300 (W) × 50 (H) × 200 (D) mm (set the UE antenna face down) Maximum test UE mass: ≤1 kg Ventilation hole: 2	
Environmental Conditions	Operating temperature range: +5° to +40°C Storage temperature range: -20° to +60°C (without condensation)	
CE	LVD	2014/35/EU, EN61010-1
	RoHS	2011/65/EU, EN50581

Anritsu OTA Products Specifications

RF Chamber MA8171A

RF Chamber MA8171A

Electrical Characteristics	<p>Shielding characteristics</p> <ul style="list-style-type: none"> ≥70 dB (800 MHz ≤ frequency ≤ 3.8 GHz) (nom.) ≥60 dB (24 GHz ≤ frequency ≤ 40 GHz) (nom.) <p>Anechoic performance</p> <ul style="list-style-type: none"> Reflected wave Level by free space standing wave ratio method in QZ (quiet zone) in φ 300 mm sphere ≥30 dB (24 GHz ≤ frequency ≤ 40 GHz) (nom.)
General	<p>External Interface</p> <ul style="list-style-type: none"> RF connection: K (f) × 2 SMA (f) × 4 UE connection: USB 2.0 (type-A) (f) × 2 Position Controller: mini D-Sub 15 pin (m) × 2 <p>Internal interface</p> <ul style="list-style-type: none"> RF connection: K (f) × 2 SMA (f) × 4 UE connection: USB 2.0 (type-A) (f) × 2 Positioner connection: mini D-Sub 15 pin (f) × 2 <p>Through sleeve pipe: 1 (φ 50 mm)</p> <p>Door: Unilateral door (left side opening)</p> <ul style="list-style-type: none"> Outside door size: 1100 (W) × 800 (H) mm Aperture: 1000 (W) × 700 (H) mm <p>Blank panel: 6</p> <p>Ventilation hole: 2</p>
Dimensions and Mass	<p>Outer dimensions: 1460 (W) × 1210 (H) × 1000 (D) mm (excluding projections)</p> <p>Effective inner dimension: 1100 (W) × 800 (H) × 650 (D) mm (Inside dimension with radio wave absorber stuck)</p> <p>Mass: ≤150 kg</p> <p>Outer dimensions (with chamber rack): 1460 (W) × 1785 (H) × 1000 (D) mm (including casters, excluding projections)</p> <p>Mass (with chamber rack): ≤240 kg</p>


Position Controller MA8174A

External Interface	<p>GPIB</p> <ul style="list-style-type: none"> Trigger output: BNC (5 V, TTL, negative logic, pulse width 20 μs) × 1 Control connector: mini D-Sub 15 pin (f) × 2 	
Dimensions and Mass	<p>Dimensions: 434 (W) × 141 (H) × 363 (D) mm</p> <p>Mass: ≤15 kg</p> <p>Rated voltage: 100 V(ac) to 120 V(ac)/200 V(ac) to 240 V(ac)</p> <p>Rated frequency: 50 Hz to 60 Hz</p> <p>Power consumption: ≤110 VA (when Positioner MA8175A connected)</p>	
Environmental Conditions	<p>Operating temperature range: +5° to +40°C (without condensation)</p> <p>Operating humidity range: ≤85% (without condensation)</p> <p>Storage temperature range: -20° to +60°C (without condensation)</p> <p>Storage humidity range: ≤85% (without condensation)</p>	
CE	EMC	2014/30/EU, EN61326-1, EN61000-3-2
	LVD	2014/35/EU, EN61010-1
	RoHS	2011/65/EU, EN50581

Anritsu OTA Products Specifications

RF Chamber MA8171A (continued)

Positioner MA8175A

<p>General</p>	<p>Axis of rotation: 2 (Theta: Horizontal rotation, Phi: Vertical rotation) Rotational speed: 1.0 rpm to 15.0 rpm, 0.1 rpm step (nom.) Rotation angle resolution (Setting resolution): 0.1 deg. (nom.) Stop precision (Reproducibility): Specified stopping precision reproducibility when the center of gravity of UE of 1 kg or less is at rotation center</p> <p>Theta: ± 0.5 deg. (nom.) Phi: ± 0.5 deg. (nom.)</p> <p>Angle of rotation Theta: -20.0 deg. to 380.0 deg. (finite rotation) Phi: 0.0 to 359.9 deg. (infinite rotation), -720.0 deg. to 720.0 deg. (finite rotation)</p> <p>Angle origin Theta: According to figure below (left) Phi: According to figure below (right)</p>  <p>Allowable torque: $10 \text{ N} \cdot \text{m}$ (nom.) UE allowable size: Tray size within 400×400 mm, 200 mm or less from the bottom of the tray UE allowable mass: 1 kg Noise: ≤ 70 dB (Conforms to Machinery Directive 2006/42/EC Annex I)</p>								
<p>External Connector</p>	<p>Theta: mini D-Sub 15 pin connector (m), 0.8 m from the end of the positioner body Phi: mini D-Sub 15 pin connector (m), 0.8 m from the end of the positioner body</p>								
<p>Dimensions and Mass Power Supply</p>	<p>Dimensions: 600 (W) \times 715 (H) \times 600 (D) mm (excluding projections and cable) Tray size: 400 (W) \times 400 (D) mm (excluding projections and screw) 70 (depth) mm (from the center of rotation to the bottom of the tray) Mass: ≤ 25 kg Power: Supplied from Position Controller MA8174A</p>								
<p>Environmental Conditions</p>	<p>Operating temperature range: $+5^\circ$ to $+40^\circ\text{C}$ (without condensation) Operating humidity range: $\leq 85\%$ (without condensation) Storage temperature range: -20° to $+60^\circ\text{C}$ (without condensation) Storage humidity range: $\leq 85\%$ (without condensation)</p>								
<p>CE</p>	<table border="1"> <tr> <td data-bbox="239 1476 395 1507">EMC</td> <td data-bbox="395 1476 1508 1507">2014/30/EU, EN61326-1, EN61000-3-2</td> </tr> <tr> <td data-bbox="239 1507 395 1539">LVD</td> <td data-bbox="395 1507 1508 1539">2014/35/EU, EN61010-1</td> </tr> <tr> <td data-bbox="239 1539 395 1570">RoHS</td> <td data-bbox="395 1539 1508 1570">2011/65/EU, EN50581</td> </tr> <tr> <td data-bbox="239 1570 395 1606">Machinery</td> <td data-bbox="395 1570 1508 1606">2006/42/EC, EN60204-1</td> </tr> </table>	EMC	2014/30/EU, EN61326-1, EN61000-3-2	LVD	2014/35/EU, EN61010-1	RoHS	2011/65/EU, EN50581	Machinery	2006/42/EC, EN60204-1
EMC	2014/30/EU, EN61326-1, EN61000-3-2								
LVD	2014/35/EU, EN61010-1								
RoHS	2011/65/EU, EN50581								
Machinery	2006/42/EC, EN60204-1								

CATR Anechoic Chamber MA8172A

CATR Anechoic Chamber MA8172A

Spurious Measurement Kit 6 GHz-60 GHz MA8172A-001

Spurious Measurement Kit 60 GHz-87 GHz MA8172A-002

Spurious Measurement Kit 6 GHz-87 GHz MA8172A-003

Test Antenna MA8172A-021

Test Antenna MA8172A-022

Electrical Characteristics	<p>Shielding characteristics: without cable connection via USB connector or Through Hole</p> <ul style="list-style-type: none"> ≥60 dB (1 GHz ≤ frequency ≤ 6 GHz) ≥60 dB (600 MHz ≤ frequency < 1 GHz, 6 GHz < frequency ≤ 87 GHz) (nom.) <p>Quiet Zone: Specifies the flatness of the amplitude and phase of the electric field in a cylindrical QZ (quiet zone) with 330 mm diameter and 330 mm depth</p> <p>Amplitude taper</p> <ul style="list-style-type: none"> MA8172A-021: ≤1.5 dB (23.4 GHz ≤ frequency ≤ 42 GHz) (nom.) MA8172A-022: ≤1.5 dB (22.65 GHz ≤ frequency ≤ 32.125 GHz) (nom.) ≤1.7 dB (32.125 GHz < frequency ≤ 45.1 GHz) (nom.) MA8172A-001: ≤3 dB (6 GHz ≤ frequency ≤ 20 GHz) (nom.) ≤1.5 dB (20 GHz < frequency ≤ 60 GHz) (nom.) MA8172A-002: ≤1.5 dB (60 GHz ≤ frequency ≤ 87 GHz) (nom.) MA8172A-003: ≤3 dB (6 GHz ≤ frequency ≤ 20 GHz) (nom.) ≤1.5 dB (20 GHz < frequency ≤ 87 GHz) (nom.) <p>Amplitude ripple</p> <ul style="list-style-type: none"> MA8172A-021: ≤1.5 dB (23.4 GHz ≤ frequency ≤ 42 GHz) (nom.) MA8172A-022: ≤1.5 dB (22.65 GHz ≤ frequency ≤ 45.1 GHz) (nom.) MA8172A-001: ≤3 dB (6 GHz ≤ frequency ≤ 20 GHz) (nom.) ≤1.5 dB (20 GHz < frequency ≤ 60 GHz) (nom.) MA8172A-002: ≤1.5 dB (60 GHz ≤ frequency ≤ 87 GHz) (nom.) MA8172A-003: ≤3 dB (6 GHz ≤ frequency ≤ 20 GHz) (nom.) ≤1.5 dB (20 GHz < frequency ≤ 87 GHz) (nom.) <p>Total phase deviation: excluding rotation of the phase distribution</p> <ul style="list-style-type: none"> MA8172A-021: ≤22.5 deg. (23.4 GHz ≤ frequency ≤ 42 GHz) (nom.) MA8172A-022: ≤22.5 deg. (22.65 GHz ≤ frequency ≤ 45.1 GHz) (nom.) <p>Connector: K-type (m), 50Ω (nom.)</p> <p>Polarization: Both (Vertical, Horizontal) (nom.)</p> <p>Maximum RF input power</p> <ul style="list-style-type: none"> 0 dBm (40 – 60 GHz, MA8172A-001) -24 dBm (MA8172A-002) -24 dBm (60 – 87 GHz, MA8172A-003)
Antenna	<p>Spurious Measurement Kit 6 GHz-60 GHz MA8172A-001</p> <p>Feed Antenna (6 – 20 GHz)</p> <ul style="list-style-type: none"> Frequency: 6 GHz to 20 GHz Connector: K-type (m) Impedance: 50Ω (nom.) Polarization: Both (Vertical, Horizontal) (nom.) <p>Feed Antenna (20 – 40 GHz)</p> <ul style="list-style-type: none"> Frequency: 20 GHz to 40 GHz Connector: K-type (m) Impedance: 50Ω (nom.) Polarization: Both (Vertical, Horizontal) (nom.) <p>Feed Antenna (40 – 60 GHz)</p> <ul style="list-style-type: none"> Frequency: 40 GHz to 60 GHz Connector: V-type (m) Impedance: 50Ω (nom.) Polarization: Both (Vertical, Horizontal) (nom.) <p>Spurious Measurement Kit 60 GHz-87 GHz MA8172A-002</p> <p>Feed Antenna (60 – 87 GHz)</p> <ul style="list-style-type: none"> Frequency: 60 GHz to 87 GHz Impedance: 50Ω (nom.) Polarization: Both (Vertical, Horizontal) (nom.) <p>Test Antenna MA8172A-021</p> <ul style="list-style-type: none"> Frequency: 23.4 GHz to 42 GHz Connector: K-type (m) Impedance: 50Ω (nom.) Polarization: Both (Vertical, Horizontal) (nom.) <p>Test Antenna MA8172A-022</p> <ul style="list-style-type: none"> Frequency: 22.65 GHz to 45.1 GHz Connector: V-type (m) Impedance: 50Ω (nom.) Polarization: Both (Vertical, Horizontal) (nom.)

Anritsu OTA Products Specifications

CATR Anechoic Chamber MA8172A (continued)

Antenna	<p>Spurious Measurement Kit 6 GHz-87 GHz MA8172A-003</p> <p>Feed Antenna (6 – 20 GHz) Frequency: 6 GHz to 20 GHz Connector: K-type (m) Impedance: 50Ω (nom.) Polarization: Both (Vertical, Horizontal) (nom.)</p> <p>Feed Antenna (20 – 40 GHz) Frequency: 20 GHz to 40 GHz Connector: K-type (m) Impedance: 50Ω (nom.) Polarization: Both (Vertical, Horizontal) (nom.)</p> <p>Feed Antenna (40 – 60 GHz) Frequency: 40 GHz to 60 GHz Connector: V-type (m) Impedance: 50Ω (nom.) Polarization: Both (Vertical, Horizontal) (nom.)</p> <p>Feed Antenna (60 – 87 GHz) Frequency: 60 GHz to 87 GHz Connector: W-type (m) Impedance: 50Ω (nom.) Polarization: Both (Vertical, Horizontal) (nom.)</p>	
General	<p>Exclusive interface Connect to MT8000A 1~6: Round multiway type connector, N (f) Connect to MA8178A (Theta, Phi): mini D-Sub 15 pin (m) For LTE Link Antenna: SMA (f) × 2</p> <p>General interface RF I/O (≤ 40 GHz): K (f) to K (f) : 2 RF I/O (≤ 18 GHz): SMA (f) to SMA (f) : 4 USB 3.0: Type-A (f) to Type-A (f) : 2 Through Hole 1: φ 50 mm Through Hole 2: □ 18 mm (four screw stopping) Through Hole 3: φ 50 mm LAN: RJ-45 (Cat 6)</p> <p>Door: Unilateral door (left side opening) Aperture: 1035 (W) × 733 (H) mm</p>	
Power Supply	<p>MA8172A Rated voltage: 100 V(ac) to 120 V(ac) / 200 V(ac) to 240 V(ac) Rated frequency: 50 Hz to 60 Hz Power consumption: ≤100 VA</p> <p>MA8172A-001 Voltage: 8 VDC</p> <p>MA8172A-002 Voltage: 8 VDC</p> <p>MA8172A-001 Voltage (60 – 87 GHz): 8 VDC</p>	
Dimensions and Mass	<p>Outer dimensions: MA8172A: 2200 (W) × 1980 (H) × 1200 (D) mm (excluding projections) MA8172A-001: 400 (W) × 100 (H) × 255 (D) mm (excluding projections and cables) MA8172A-002: 90 (W) × 60 (H) × 175 (D) mm (excluding projections and cables) MA8172A-003: 350 (W) × 145 (H) × 255 (D) mm (excluding projections and cables) MA8172A-021: 90 (W) × 60 (H) × 175 (D) mm (excluding projections and cables) MA8172A-022: 50 (W) × 50 (H) × 150 (D) mm (excluding projections and cables)</p> <p>Mass: MA8172A: ≤700 kg (including all options, excluding rack) MA8172A-001: ≤10 kg MA8172A-002: ≤1 kg MA8172A-003: ≤11 kg MA8172A-021: ≤1 kg MA8172A-022: ≤1 kg</p>	
Environmental Conditions	<p>Operating temperature range: +5° to +35°C (MA8172A, MA8172A-001/-002/-003/-021/-022, without condensation) Operating humidity range: ≤85% (MA8172A-001/-002/-003, without condensation) Storage temperature: -20° to +60°C (MA8172A, MA8172A-001/-002/-003/-021/-022, without condensation)</p>	
CE	EMC	2014/30/EU, EN61326-1, EN61000-3-2
	LVD	2014/35/EU, EN61010-1
	RoHS	2011/65/EU, EN50581



Anritsu OTA Products Specifications

CATR Anechoic Chamber MA8172A (continued)

Position Controller MA8178A

External Interface		Ethernet: RJ-45 × 1 (1000Base-T) Trigger Out: BNC × 1 (5 V, TTL, negative logic, pulse width 20 μs) Control connector Theta: mini D-Sub 15 pin (f) × 1 Phi: mini D-Sub 15 pin (f) × 1
Dimensions and Mass		Dimensions: 434 (W) × 180 (H) × 210 (D) mm Mass: ≤15 kg Rated voltage: 100 V(ac) to 120 V(ac)/200 V(ac) to 240 V(ac) Rated frequency: 50 Hz to 60 Hz Power consumption: ≤200 VA (when Positioner MA8179A connected)
Environmental Conditions		Operating temperature range: +5° to +40°C (without condensation) Operating humidity range: ≤80% (without condensation) Storage temperature range: -20° to +60°C (without condensation) Storage humidity range: ≤80% (without condensation)
CE	EMC	2014/30/EU, EN61326-1, EN61000-3-2
	LVD	2014/35/EU, EN61010-1
	RoHS	2011/65/EU, EN50581

Positioner MA8179A

General		<p>Axis of rotation: 2 (Theta: Horizontal rotation, Phi: Vertical rotation) Rotational speed: 0.1 rpm to 10.0 rpm, 0.1 rpm step (nom.) Rotation angle resolution (Setting resolution): 0.1 deg. (nom.) Stop precision (Reproducibility): Specified stopping precision reproducibility when the center of gravity of UE of 1 kg or less is at rotation center Theta: ±0.5 deg. (nom.) Phi: ±0.5 deg. (nom.) Angle of rotation Theta: -20.0 deg. to 380.0 deg. (finite rotation) Phi: infinite rotation Angle origin Theta: According to figure below (left) Phi: According to figure below (right)</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>Door side</p> </div> <div style="text-align: center;">  <p>Front view</p> </div> </div> <p>EUT allowable size: 330 mm diameter hemisphere around the axis of rotation EUT allowable mass: 2.0 kg Noise: ≤70 dB (Conforms to Machinery Directive 2006/42/EC Annex I) Power: Supplied from Position Controller MA8178A</p>
Dimensions and Mass		Dimensions: 600 (W) × 360 (H) × 600 (D) mm (excluding projections and cables) Mass: ≤15 kg
Environmental Conditions		Operating temperature range: +5° to +40°C (without condensation) Operating humidity range: ≤80% (without condensation) Storage temperature range: -20° to +60°C (without condensation) Storage humidity range: ≤80% (without condensation)
CE	EMC	2014/30/EU, EN61326-1, EN61000-3-2
	LVD	2014/35/EU, EN61010-1
	RoHS	2011/65/EU, EN50581
	Machinery	2006/42/EC, EN60204-1

Anritsu OTA Products Ordering Information

Please specify the model/order number, name and quantity when ordering.

The names listed in the chart below are Order Names. The actual name of the item may differ from the Order Name.

Model/Order No.	Name
	Shield Box
MA8161A	Shield Box
MA8161A-001	Control Panel 1
MA8161A-002	Control Panel 2
MA8161A-AK010	Shield Tube
Z1999A	28 GHz Antenna Unit
Z2000A	39 GHz Antenna Unit
K241C	Precision Power Splitter, DC to 40 GHz
	RF Chamber
MA8171A	RF Chamber
MA8174A	Position Controller
MA8175A	Positioner
MA8175A-AK001	Cable Management Kit
MA8181A	28 GHz Test Antenna
Z1996A	28 GHz/39 GHz Test Antenna
Z2031A	Test Antenna
B0746A	Chamber Rack
B0747A	Converter Rack
J0322A	Coaxial Cord, 0.5M
J0322B	Coaxial Cord, 1.0M
J0322C	Coaxial Cord, 1.5M
J0322D	Coaxial Cord, 2.0M
J1762A	Positioner Control Cable (3.0 m)
J1775A	Coaxial Cable (KM-KM, 0.3 m)
J1775B	Coaxial Cable (KM-KM, 1.0 m)
J1775C	Coaxial Cable (KM-KM, 2.0 m)
J1775D	Coaxial Cable (KM-KM, 3.0 m)
J1795A	Coaxial Cable (SMA (M)-SMA (M), 0.5 m)
J1795B	Coaxial Cable (SMA (M)-SMA (M), 1.0 m)
J1795C	Coaxial Cable (SMA (M)-SMA (M), 1.5 m)
J1795D	Coaxial Cable (SMA (M)-SMA (M), 2.0 m)
J1811A	Coaxial cable (VM-VM, 0.28 m)
J1811B	Coaxial cable (VML-VM 2.5 m)
Z1983A	Tray
Z1984A	Jig for DUT Tray
Z1985A	Wave Absorber
Z1986A	Hook and Loop Fastener
Z2009A	Link Antenna
B0752A	Link Antenna Holder
J1798A	GPIO-USB-HS+
J1806A	VJ-VJ Adaptor
J1806B	VJ-KJ Adaptor

Model/Order No.	Name
	CATR Anechoic Chamber
MA8172A	CATR Anechoic Chamber
MA8172A-001	Spurious Measurement Kit 6 GHz-60 GHz
MA8172A-002	Spurious Measurement Kit 60 GHz-87 GHz
MA8172A-003	Spurious Measurement Kit 6 GHz-87 GHz
MA8172A-021	Test Antenna
MA8172A-022	Test Antenna
MA8172A-AK011	Converter Install Kit
MA8172A-AK012	Converter Tray
MA8172A-AK013	Switching Hub
MA8172A-AK022	NR FR2 Link Antenna Kit
MA8172A-AK023	LTE Link Antenna Kit
MA8172A-AK031	Monitor Camera
MA8172A-AK032	Additional Rack (41U)
MA8178A	Position Controller
MA8179A	Positioner
Z1974A	Reference Antenna
Z2032A	Reference Antenna
J1806D	VJ-KP Adaptor
J1811B	Coaxial cable (VML-VM, 2.5 m)
ML2437A	Power Meter
MA2444D	High Accuracy Sensor
MA2445D	High Accuracy Sensor
41KC-10	Fixed Attenuator
41V-10	Fixed Attenuator
34VFK50A	Precision Adapter, DC to 43.5 GHz, V (f) - K (m), 50Ω

Anritsu OTA Products Related Products

Radio Communication Test Station MA8000A



All-in-One 5G RF Measurements and Protocol Tests

- Flexible Platform using Modular Architecture
- Support both Standalone and non-Standalone modes

New Radio RF Conformance Test System ME7873NR



Trust 5G conformance test system

- Early 3GPP Compliant Test Case Release
- Support Global Mobile Terminals
- The System with Stable Measurement
- Measurement Functions for Efficient R&D

5G NR Mobile Device Test Platform ME7834NR



All-in-One 5G NR Support for Protocol Conformance Tests and Carrier Acceptance Test

- Supports 3GPP defined bands from Sub-6GHz to mm-Wave
- Support 5G New Radio (NR) Technology in both Standalone and Non-Standalone mode
- Support LTE, LTE-Advanced (LTE-A), LTE-A Pro, and W-CDMA
- Upgrade your current ME7834 system for 5G



Anritsu envision:ensure

Specifications are subject to change without notice.

• United States

Anritsu Americas Sales Company

450 Century Parkway, Suite 190, Allen,
TX 75013 U.S.A.
Phone: +1-800-Anritsu (1-800-267-4878)

• Canada

Anritsu Electronics Ltd.

700 Silver Seven Road, Suite 120, Kanata,
Ontario K2V 1C3, Canada
Phone: +1-613-591-2003
Fax: +1-613-591-1006

• Brazil

Anritsu Elettronica Ltda.

Praça Amadeu Amaral, 27 - 1 Andar
01327-010 - Bela Vista - Sao Paulo - SP
Brazil
Phone: +55-11-3283-2511
Fax: +55-11-3288-6940

• Mexico

Anritsu Company, S.A. de C.V.

Bldv Miguel de Cervantes Saavedra #169 Piso 1, Col. Granada
Mexico, Ciudad de Mexico, 11520, MEXICO
Phone: +52-55-4169-7104

• United Kingdom

Anritsu EMEA Ltd.

200 Capability Green, Luton, Bedfordshire, LU1 3LU, U.K.
Phone: +44-1582-433200
Fax: +44-1582-731303

• France

Anritsu S.A.

12 avenue du Québec, Bâtiment Iris 1- Silic 612,
91140 VILLEBON SUR YVETTE, France
Phone: +33-1-60-92-15-50
Fax: +33-1-64-46-10-65

• Germany

Anritsu GmbH

Nemetschek Haus, Konrad-Zuse-Platz 1
81829 München, Germany
Phone: +49-89-442308-0
Fax: +49-89-442308-55

• Italy

Anritsu S.r.l.

Via Elio Vittorini 129, 00144 Roma, Italy
Phone: +39-6-509-9711
Fax: +39-6-502-2425

• Sweden

Anritsu AB

Isafjordsgatan 32C, 164 40 KISTA, Sweden
Phone: +46-8-534-707-00

• Finland

Anritsu AB

Teknobulevardi 3-5, FI-01530 VANTAA, Finland
Phone: +358-20-741-8100
Fax: +358-20-741-8111

• Denmark

Anritsu A/S

Torveporten 2, 2500 Valby, Denmark
Phone: +45-7211-2200
Fax: +45-7211-2210

• Russia

Anritsu EMEA Ltd.

Representation Office in Russia

Tverskaya str. 16/2, bld. 1, 7th floor.
Moscow, 125009, Russia
Phone: +7-495-363-1694
Fax: +7-495-935-8962

• Spain

Anritsu EMEA Ltd.

Representation Office in Spain

Edificio Cuzco IV, Po. de la Castellana, 141, Pta. 5
28046, Madrid, Spain
Phone: +34-915-726-761
Fax: +34-915-726-621

• United Arab Emirates

Anritsu EMEA Ltd.

Dubai Liaison Office

902, Aurora Tower,
P O Box: 500311 - Dubai Internet City
Dubai, United Arab Emirates
Phone: +971-4-3758479
Fax: +971-4-4249036

• India

Anritsu India Private Limited

6th Floor, Indiqube ETA, No.38/4, Adjacent to EMC2,
Doddanekundi, Outer Ring Road, Bengaluru - 560048, India
Phone: +91-80-6728-1300
Fax: +91-80-6728-1301

• Singapore

Anritsu Pte. Ltd.

11 Chang Charn Road, #04-01, Shriro House
Singapore 159640
Phone: +65-6282-2400
Fax: +65-6282-2533

• P.R. China (Shanghai)

Anritsu (China) Co., Ltd.

Room 2701-2705, Tower A,
New Caohejing International Business Center
No. 391 Gui Ping Road Shanghai, 200233, P.R. China
Phone: +86-21-6237-0898
Fax: +86-21-6237-0899

• P.R. China (Hong Kong)

Anritsu Company Ltd.

Unit 1006-7, 10/F., Greenfield Tower, Concordia Plaza,
No. 1 Science Museum Road, Tsim Sha Tsui East,
Kowloon, Hong Kong, P.R. China
Phone: +852-2301-4980
Fax: +852-2301-3545

• Japan

Anritsu Corporation

8-5, Tamura-cho, Atsugi-shi, Kanagawa, 243-0016 Japan
Phone: +81-46-296-6509
Fax: +81-46-225-8352

• Korea

Anritsu Corporation, Ltd.

5FL, 235 Pangyo-yeok-ro, Bundang-gu, Seongnam-si,
Gyeonggi-do, 13494 Korea
Phone: +82-31-696-7750
Fax: +82-31-696-7751

• Australia

Anritsu Pty. Ltd.

Unit 20, 21-35 Ricketts Road,
Mount Waverley, Victoria 3149, Australia
Phone: +61-3-9558-8177
Fax: +61-3-9558-8255

• Taiwan

Anritsu Company Inc.

7F, No. 316, Sec. 1, NeiHu Rd., Taipei 114, Taiwan
Phone: +886-2-8751-1816
Fax: +886-2-8751-1817